

**MAXCLEAN® -R**

GEL FOR PAINT ELIMINATION

DESCRIPTION

High concentration paint removal gel, surfactant, formulated to eliminate synthetic paints as a powerful coating stripper.

USES

Serves to remove:

- Solvent based polyurethane
- Water based polyurethane
- Water based epoxy
- Solvent based epoxy
- Solvent free epoxy
- Acrylic
- Vinyl Veova
- Acrylic-Styrene
- Enamel
- Classical solvent based varnish
- Alchidyc
- Chlorinated rubber

ADVANTAGES.

- Great penetrating power through several layers of paint or coatings.
- Does not contain acids or alkalis
- Low evaporation index, increasing its active life, preventing paint from bonding again during removal.
- Quick acting, reduces scraping, sanding, wirebrushing or shot blasting work.
- Surfactant

APPLICATION

It is applied by brush, roller or spatula on the surface to be cleaned. Allow to act for 10 to 15 minutes until the paint layer wrinkles. Apply in a thick layer both on horizontal and vertical surfaces. Finally remove with spatula, rag cloth, high pressure water jet or wire brush. Repeat as many times as necessary. It is advisable to allow the clean surface to dry well, and wash it if it is possible before coating anew.

PREPARATION OF THE SURFACE.

The surface does not require any special prior treatment, although a light sanding can be convenient.

TECHNICAL DATA

Colour:	Milky transparent.
Density (kg / lt):	1,150 ± 0,050
Viscosity (mPas):	8500 ± 2500

COVERAGE

2 to 6 m² / kg.

TOOL CLEANING.

With abundant clean water.

PACKAGING

5 kg. can.

STORAGE

Twelve months in its original unopened container.

SAFETY

- Avoid contact with the eyes and skin. Use adequate clothing, rubber gloves and protective goggles and masks.
- Avoid inhalation (very toxic), contains methylene chloride
- Keep away from fire and the reach of children.
- In interiors, apply with good air renovation, using appropriate mask when ventilation conditions are not satisfactory.
- Flammable.
- On hot days, open the container with the face away from its lid.
- If it comes in contact with the skin, wash with warm water and soap, in case of contact with the eyes, rinse with abundant water, at least during 15 minutes and seek urgent medical help.

R and S PHRASES.

R40	Possibility of irreversible effects.
S2	Keep out of the reach of children.
S23	Do not breathe gases/fumes/vapours/aerosols (appropriate denomination (S) specified by the manufacturer).
S24/25	Avoid contact with the eyes and skin.
S36/37	Use appropriate protective gloves and clothing.

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. DRIZORO reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product.



DRIZORO, S.A.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13

e-mail: info@drizoro.com Web site: drizoro.com

