



BISEALTM MRL - F

WATER BORNE MOULD REMOVING LIQUID FOR METAL FORMS

DESCRIPTION

BISEAL MRL - F is an oil emulsified in a waterbase, for the removal of metal plank or board forms, for concrete placed on site.

USES

- Removing of metallic forms for concrete, on site with metal forms, as well as any type of moulds, allowing perfect de-moulding of the piece.

ADVANTAGES

- Easy de-moulding of the concrete element.
- High non-stick effect.
- Its great capacity to cover the surface eases the application preventing the adhesion of concrete.

APPLICATION INSTRUCTIONS

Preparation of the substrate. The metal form must be dry, free from cement powder, dust, removing any leftovers from previous de-mouldings, grease, rust and any other foreign matter.

Application.

The product is supplied ready to use. It is applied using a brush, roller or spray gun with a nozzle which forms a flat fan to prevent excessive applications, until the metal form is completely coated, in one or two applications. Allow between 15 to 30 minutes before placing the concrete.

COVERAGE

4.0 to 8.0 m² / litre

CAUTIONS

- Excessive amounts can cause staining of the concrete.
- Make the application homogeneous on the entire mould surface.

SAFETY

- BISEAL MRL - F is not a toxic product, but when applying keep in mind not to use the hands without the protection of rubber gloves or protective glasses. If the product comes in contact with the eyes, rinse with abundant clean water but do not rub. If the irritation persists, consult a doctor.

PACKAGING

220 litre drums and 20 litre jerrycans.

STORAGE

Twelve months in its original unopened container, in a dry covered place and temperatures above 4°C.

TECHNICAL DATA

Density (kg / dm ³)	0.94 ± 0.01
Colour	Milky

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. DRIZORO reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product.



DRIZORO, S.A.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13

e-mail: info@drizoro.com Web site: drizoro.com

