



BISEAL[®] FS

SETTING ACCELERATOR ADDITIVE FOR CONCRETE AND MORTARS

DESCRIPTION

BISEAL FS is a setting accelerator additive for concrete and mortars, without chlorides.

USES

Preparation of concrete, with or without reinforcement, and mortars which require fast setting.

- Concrete placing in water environments. (marine or sweet)
- Prefabrication of elements for fast mould removal.

ADVANTAGES

- The fast setting provided, improves the behaviour of concrete when placed at low temperatures.
- Provides homogeneity to concrete and mortar preventing the segregation of its components.
- Increases the rotation of moulds, both on site and for prefabrication, thus improving productivity.

APPLICATION INSTRUCTIONS

Mixing of the product.

BISEAL FS is added directly to the mixing water.

Dosage and consumption.

Dosage is done by volume in dilutions of BISEAL FS : water of between 1:3 to 1:6. (Between 25% and 14% of the mixing water)

It is advised to do a trial previously to determine the adequate amount depending on the setting time required.

CAUTIONS

- Minimum cement content of concrete of at least 300kg/m³.
- To avoid wasting material, it is advised to prepare the amount of concrete or mortar that can be placed in the foreseen setting time.
- Make sure sufficient means are available for the placing of the concrete in the allotted time.
- Final strengths obtained are slightly below those of unmodified concrete or mortar.

PACKAGING

20 litre plastic jerrycans.

STORAGE

Twelve months in its original unopened container in a dry covered place and at temperatures above – 5 °C.

SAFETY

Avoid contact with the eyes and skin.

Use rubber gloves and safety goggles.

If it comes in contact with the skin, wash with warm water and soap.

If it comes in contact with the eyes rinse thoroughly with water and seek medical assistance.

TECHNICAL DATA

Colour	Transparent
Appearance	Liquid
pH	13

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. DRIZORO reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product.



DRIZORO, S.A.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13

e-mail: info@drizoro.com Web site: drizoro.com

