



BISEALTM PL

PLASTICISING ADDITIVE FOR CONCRETE AND MORTARS

DESCRIPTION

BISEAL PL is a concentrated plasticiser to improve workability of concrete and mortars

USES

It is used both for concrete and mortars whether rich or poor in cement content.

ADVANTAGES

- High efficiency concentrated product.
- Aids the workability.
- Provides cohesion to the mix, preventing segregation.
- Reduces shrinkage in cement rich mortars and concrete.
- Its slight foaming action breaks the capillary net in mortars and concrete increasing their frost resistance.
- Can be used to reduce the mixing water.

APPLICATION INSTRUCTIONS

It can be added directly to the mixing water at a rate of 0.1% to 0.2% by weight of cement. Cleaning is done with abundant clean water.

CAUTIONS

- Avoid contact with the eyes and skin.
- Use safety goggles and rubber gloves.
- In case of contact with the skin, wash with luke-warm water and soap.
- In case of contact with the eyes, rinse thoroughly with water seek medical assistance.
- It is a non-flammable product.

PACKAGING

20 litre jerrycans.

CONSUMPTION

50 cm³ to 100 cm³ per each 50 kg. cement bag.

STORAGE

Twelve months in its original unopened container, in a dry covered place with temperatures above 4°C.

TECHNICAL DATA

Density (gr/cm3) at 20°C	1.03 ± 0.05
Colour	Yellowish
Solubility in water	Complete
pH	7 ÷ 0,5
Appearance	Fluid

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. DRIZORO reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product.



DRIZORO, S.A.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13

e-mail: info@drizoro.com Web site: drizoro.com

