



MAXCRYL®

LIQUID ADDITIVE TO IMPROVE BONDING AND CURING OF MORTARS AND CONCRETE

DESCRIPTION

MAXCRYL is a white, acrylic-base product used as an additive for portland cement mortars and concrete to increase adhesion and mechanical properties. Mortars prepared with MAXCRYL are more manageable, have greater compactness, longer setting and application time, and greater strength, compression and tension.

APPLICATIONS

MAXCRYL gives concrete and mortars, as well as MAXSEAL, CONCRESEAL PLASTERING and other DRIZORO products, greater adherence to smooth surfaces. MAXCRYL gives the above mentioned products a better cure when temperatures are high. As an additive for mortars in rehabilitation work, MAXCRYL keeps shrinkage to a minimum and increases adherence to smooth surfaces.

HOW TO USE FOR REPAIRS

Preparation of the surface.

The surface must be clean. There must be no loose particles, paint, grease, etc. If necessary, use sandblasting or water blast to clean the surface.

Preparing the mortar.

Mix the cement and sand in the required proportions. In a separate container mix one part MAXCRYL to three parts water.

Once the semi-dry mortar has been mixed, apply it without pressing too hard with the trowel. Apply the mortar in layers.

Allow patch to cure for seven days before painting over.

MAXCRYL RATIOS FOR DIFFERENT APPLICATIONS

With MAXSEAL-CONCRESEAL PLASTERING.

A ratio of 1:3 One part MAXCRYL to three parts water.

With cement mortars.

A ratio of 1: 3 or a ratio of 1: 2 depending on the job.

You can also experiment with other ratios before undertaking a specific job, to make sure that such ratio meets the specific requirement.

CAUTION

While handling or storing, keep MAXCRYL from reaching temperatures below 0 °C, to avoid freezing. The product is stable at up to five freeze thaw cycles. Do not apply mixes with MAXCRYL

as an additive at temperatures below 5 °C, or when the temperature is expected to drop to such level within 24 hours.

PACKAGING

220 litre drums, 20, 5 and 2 litre jerrycans.

STORAGE

18 months in its original, unopened containers, in a dry covered place protected from frost.

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. DRIZORO reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product.



DRIZORO, S.A.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13

e-mail: info@drizoro.com Web site: drizoro.com

